

DIGITAL PORTION SCALES

Models PS-7 and PS-11

MODEL PS-7

The smooth lines of the molded poly enclosure, lift-off stainless steel commodity tray, and sealed membrane keypad make cleaning the PS-7 easy. Capacity: 7 lb x 0.1 oz, 112 oz x 0.1 oz, 112 oz x 1/8 oz, 3000 g x 1 g, 7 lb x 0.005 lb

Built-in Rechargeable Battery

NSF

MODEL PS-11

Enjoy the durability of the rugged PS-11 stainless steel all-purpose bench and counter top scale which can switch between five units of measurement at the push of a button. Capacity: 11 lb x 0.1 oz, 176 oz x 0.1 oz, 176 oz x 1/4 oz, 5000 q x 2 q, 11 lb x 0.005 lb



DIGITAL PORTION SCALES

PS-11

• Easy-To-Read LCD Display

• Power-Saving "Auto-off" Feature

• IP52 Water Resistant Enclosure

Switch Selectable Units

NSF Certified

Disable Different Units of Measure

• Easy-To-Clean, Removable Stainless Steel Tray



Ideal for:

Food Service Operations • Industrial Applications Chemical Industry • Retail Establishments (food, drug)

	PS-11 SPECIFICATIONS
Capacity	11 lb x 0.1 oz, 176 oz x 0.1 oz, 176 oz x 1/4 oz, 5000 g x 2 g, 11 lb x 0.005 lb
Display	5-digit, 0.8" x 0.3" characters with fractions LCD digital display
Dimensions	7.48"W x 9.84"D x 2.17"H 190mm W x 250mm D x 55mm H
Platform Size	6.89"W x 6.5"D (175mm W x 165mm D)
Construction	Stainless steel with stainless steel commodity tray
Tare	100% of full scale capacity
Keys	ON/OFF, ZERO, UNITS
Zero	Established on power up routine and maintained by auto-zero circuitry
Temperature	40° to 105° F (5° to 40° C)
Humidity	25% ~95% RH
Power	Built-in rechargeable battery pack included (7.2 VDC/1200mA) or 115 VAC 50/60 Hz or 230 VAC 50/60 Hz powering a 15 VDC 300mA wall plug-in UL/CSA listed power supply.
Features	 Power-saving selectable timing auto shut-off which only goes to sleep when using battery operation. Low battery indicator. Rechargeable battery pack is able (after 8 hours of charging) to provide up to 24 hours of continuous use, making it ideal as a portable scale.

Ideal for:

Restaurants • Cafeterias • Deli's • Pizza Parlors Food Service Professionals (industrial)

PS-7 SPECIFICATIONS		
Capacity	7 lb x 0.1 oz, 112 oz x 0.1 oz, 112 oz x 1/8 oz, 3000 g x 1 g, 7 lb x 0.005 lb	
Display	5-digit, 0.8" x 0.3" characters with fractions LCD digital display	
Dimensions	8.03"W x 7.87" D x 2.44" H 204mm W x 200mm D x 62mm H	
Platform Size	8.02"W x 4.96" D (204mm W x 126mm D)	
Construction	Molded poly enclosure with stainless steel commodity tray	
Tare	100% of full scale capacity	
Keys	ON/OFF, ZERO, UNITS	
Zero	Established on power up routine and maintained by auto-zero circuitry	
Temperature	40° to 105° F (5° to 40° C)	
Humidity	25% ~95% RH	
Power	115 VAC 50/60 Hz or 230 VAC 50/60 Hz powering a 15 VDC 300 mA wall plug-in UL/CSA listed power supply or one (1) 9 VDC Alkaline battery (battery not included).	
Features	 Power-saving selectable timing auto shut-off which only goes to sleep when using battery operation. Low battery indicator. 	

Stable weight annunciator -

lb, oz, lb-oz, oz-1/4, and g-annunciators



Switch selectable units button

Pushbutton zero key Zero also established during setup

The PS-7 and PS-11 are NSF Certified

 $Cardinal\ Scale\ reserves\ the\ right\ to\ improve, enhance\ or\ modify\ features\ and\ specifications\ without\ prior\ notice.\ All\ registered\ trademarks\ are\ the\ property\ of\ their\ respective\ owners.$

DETECTO®

A Division of Cardinal Scale Manufacturing Co.

203 E. Daugherty, Webb City, MO 64870 USA
Ph: 417-673-4631 or 1-800-641-2008 Fax: 417-673-5001

www.detectoscale.com

SOLD BY: