



**PRODUCT SPECIFICATIONS**

## Digital Dough Scales for Digital Accuracy and Precise Portion Control



Choose from three capacities and three sizes of stainless steel bases to fit your needs.

### PZ 2500

*Your best general purpose selection.*

#### Specifications

Capacity: 25 lb x 1/4 oz (11.34 kg x .005 kg)  
 Base: 12"W x 12"D x 1 7/8"H  
 Display: 5-digit, 0.7" LCD digital  
 7 1/2"W x 1 1/2"D x 4 1/2"H  
 Power: 115 VAC, 50/60 Hz or 230 VAC  
 50/60 Hz powering a 12 VDC 300  
 mA wall plug-in. UL/CSA listed  
 power supply or six (6) AA Ni-Cad  
 batteries (not included)  
 Tare: On/Zero key on keypad or foot  
 tare switch with 8' cable  
 Temperature: 30° to 110°F (-1° to 43°C)

### PZ 2514

*All specifications, except base dimensions and capacity, are the same as PZ2500.*

#### Specifications

Capacity: 60 lb x 1/4 oz (27.22 kg x .005 kg)  
 Base: 12"W x 14"D x 3"H

### PZ 1025

*The real cutting edge in precise portion control.  
 Includes foot tare pedal. AC powered.*

#### Specifications

Capacity: 200 oz x 0.1 oz (5 kg x .005 kg)  
 Base: 8"W x 8"D x 1 7/8"H  
 Display: 4-digit, 0.5" LED digital  
 6 7/8"W x 1 7/16"D x 3 3/8"H  
 Power: 115 VAC, 50/60 Hz or 220 VAC  
 50/60 Hz; AC adapter with 6' cord  
 Tare: Foot tare switch with 8' cable  
 Temperature: 30° to 110°F (-1° to 43°C)

### PZ 2525

*Full function, compact size for limited space.*

#### Specifications

Capacity: 25 lb x 1/4 oz (11.34 kg x .005 kg)  
 Base: 8"W x 8"D x 1 7/8"H  
 Display: 5-digit, 0.7" LCD digital  
 7 1/2"W x 1 1/2"D x 4 1/2"H  
 Power: 115 VAC, 50/60 Hz or 230 VAC  
 50/60 Hz powering a 12 VDC 300  
 mA wall plug-in. UL/CSA listed  
 power supply or six (6) AA Ni-Cad  
 batteries (not included)  
 Tare: On/Zero key on keypad or foot  
 tare switch with 8' cable  
 Temperature: 30° to 110°F (-1° to 43°C)

Cardinal Scale reserves the right to improve, enhance and modify features and specifications without prior notice.